



※ Including Screw Plug 附止付螺絲

A Type 品名	Material 材質	Hardness 硬度	Delivery 交貨日
HTPS002	SKD61	40HRC~	8 Working Days 8 個工作日

B Spring constant 彈性常數
0.98N/mm(0.1kgf/mm)

Type 品名	Punch blank 適用沖頭	b Punch length 適用沖頭長度								B- Spring length 彈簧長度												d1				
		A-		b						d		D		H		T		WL30		WL35			WL40		WL50	
		40L	50L	60L	70L	80L	90L	100L	d	D	H	T	Wire diameter 線徑	Fmax	Wire diameter 線徑	Fmax	Wire diameter 線徑	Fmax	Wire diameter 線徑	Fmax	Wire diameter 線徑	Fmax	Wire diameter 線徑	Fmax	Wire diameter 線徑	Fmax
HTPS002	5	20	30	30	40	50	60	70	0.65	1.9	4	3	0.55	12	0.55	14	0.6	16	0.6	20	0.6	24	0.6	24	4	
	6	20	30	30	40	50	60	70	0.65	2.3	4.5	3	0.55	12	0.55	14	0.6	16	0.6	20	0.6	24	0.6	24	4	
	8	20	35	40	40	50	60	70	1.05	3.1	9	3	0.7	12	0.7	14	0.7	16	0.75	20	0.75	24	0.75	24	6	
	10	20	35	40	40	50	60	70	1.4	3.9	8	4	0.8	12	0.8	14	0.8	16	0.85	20	0.85	24	0.85	24	8	
	13	20	35	40	40	50	60	70	1.7	3.9	8	4	0.8	12	0.8	14	0.8	16	0.85	20	0.85	24	0.85	24	8	
	16、20、25	20	35	40	40	50	60	70	2.7	3.9	8	4	0.8	12	0.8	14	0.8	16	0.85	20	0.85	24	0.85	24	8	

Type 品名	Punch blank 適用沖頭	L Punch length 適用沖頭長度								B- FL	C Screw Plug (MxP)
		40L	50L	60L	70L	80L	90L	100L			
HTPS002	5	41	51	61	71	81				30/35/40/50/60	M5x0.8
	6	41	51	61	71	81				30/35/40/50/60	M6x1.0
	8	41.5	51.5	61.5	71.5	81.5	91.5	101.5		30/35/40/50/60	M8x1.25
	10	41.5	51.5	61.5	71.5	81.5	91.5	101.5		30/35/40/50/60	M10x1.5
	13	41.5	51.5	61.5	71.5	81.5	91.5	101.5		30/35/40/50/60	M10x1.5
	16、20、25	42	52	62	72	82	92	102		30/35/40/50/60	M10x1.5

Order Ex. 訂購範例

HTPS002-d-L-FL



外徑  
導柱長度  
彈簧長度