



Type 品名	Material 材質	Heat Treatment 熱處理	Hardness 硬度	Delivery 交貨日
SZ-DMWT	S45C	Surface Hardened 高頻淬火	HRC 55~	8 Working Days 8 個工作日

Type	W	L	Hole Type	ℓ1	ℓ2	ℓ3	VDI Code			
SZ-DMWT	30	80	A	55	-	-	VDI3357-B-252			
		100		75	VDI3357-B-253					
		125		100	VDI3357-B-254					
		160		135	VDI3357-B-255					
		200		175	VDI3357-B-256					
		225		200	VDI3357-B-256					
	40	80	A	55	-	-	VDI3357-B-262			
		100		75	VDI3357-B-263					
		125		100	VDI3357-B-264					
		160		135	VDI3357-B-265					
		200		175	VDI3357-B-266					
		225		200	VDI3357-B-266					
	40	240	B	85	155	215	-			
		250		165	225					
		260		175	235					
		280		195	255					
		50		80	A	55		-	-	VDI3357-B-272
				100		75		VDI3357-B-273		
	125		100	VDI3357-B-274						
	160		135	VDI3357-B-275						
	180		155	-						
	200		175	VDI3357-B-276						
	50	225	200	VDI3357-B-276						
		240	B	85	155	215	-			
250		165		225						
260		175		235						
280	195	255								

Type	W	L	Hole Type	ℓ1	ℓ2	ℓ3	VDI Code			
SZ-DMWT	60	80	A	55	-	-	VDI3357-B-282			
		100		75	VDI3357-B-283					
		125		100	VDI3357-B-284					
		160		135	VDI3357-B-285					
		200		175	VDI3357-B-286					
		225		200	VDI3357-B-286					
		80	240	B	85	155	215	-		
			250		165	225				
			260		175	235				
			280		195	255				
			300		105	195	275			
			320		215	295				
			340	235	315					
			350	125	225	325				
			100	80	A	55	-		-	VDI3357-B-292
				100		75	VDI3357-B-293			
				125		100	VDI3357-B-294			
				160		135	VDI3357-B-295			
	200	175		VDI3357-B-296						
	225	200		VDI3357-B-296						
	80	240		B	85	155	215	-		
		250			165	225				
		260			175	235				
		280			195	255				
		300			105	195	275			
		320			215	295				
		340		235	315					
		350		125	225	325				
		100		250	B	85	165		225	-
				280		85	195		255	
				300		105	195		275	
				320		105	215		295	
	340		105	235		315				
	350		125	225		325				

Order Ex. 訂購範例

SZ-DMWT-W-L